



### SA-5 Servo Attaching Feeder

#### Precision attaching in a small package!

# Finally, a compact, affordable attaching solution that fits your budget *AND* your transport.

The Straight Shooter SA-5 attaching feeder was designed to fit where other attaching feeders won't. Its small footprint and simple design allow you to use it on a wide variety of transport bases.

Servo technology offers precise positioning and the color touch screen gives the operator complete control of the job settings.

The SA-5 can attach 1 or 2 cards, magnets, or other media at speeds up to 25,000 per hour! (media dependent)

Utilizing our patented *Buckle Separation*<sup>™</sup> technology, the SA-5 feeds a wide variety of materials easily and our re-positional feed belts offer unmatched flexibility!

Feeders for mailing, printing and packaging

# SA-5 Servo

One or two card attaching

Batch counting for packaging

Turn-key package includes feeder, controller, touch screen, encoder and start photo!

# Finally, an attaching feeder for the rest of us!

Straight Shooter is known for innovation and the SA-5 continues the tradition. <u>Until now</u>, servo attaching feeders have been oversized, complicated and EXPENSIVE! *Not the SA-5!* 

The SA-5 is compact, easy to use and affordable. Now you don't have to be an engineer to handle attaching! Our color touch screen and patented features make precision attaching easier than ever.







#### Straight Shooter makes high speed attaching easier with these exclusive features:

- \* Re-positional Feed Belts -- Lets you customize the feeder for every piece!
- \* Independently Adjustable Separators Patented Buckle Separation reduces jams!
- \* Easy to service <u>ALL</u> belts can be replaced in minutes!
- \* Compact size Fits where others won't!
- \* Adjustable angle acceleration table
- \* Simple set up for 1 or 2 cards
- \* High speed batch counting
- \* Intuitive, easy to use
- \* Attaches dual cards as close together as you want!

Turn-key package includes:

Color touch screen High speed servo motor Controller for servo system Start and stop photo eyes Encoder with wheel and bracket Knock down roller assembly Specifications

Media Handling: Width: 2" minimum up to 5" maximum Length: 2" minimum up to 12" maximum Thickness: Single sheet up to 1/4" thick Speeds: Up to 25,000 single cards attached per hour Placement accuracy: 1/8" plus or minus\* \*Operator, media and transport dependent

Power:

120 vac, 5 amp standard, (240 optional) Miss output standard. (used to stop transport base or host feeder on feeder out condition)

Dimensions: 8" wide x 17" long (excluding knock down rollers)



Straight Shooter Equipment Company (800) 785-4177 www.feedstraight.com Authorized Distributor: